



THERMOPLASTIC PAINT

DESCRIPTION

EVICO Thermoplastic paint are premium quality road marking paint.

RECOMMENDED USES



Suitable for exterior use.

Roads, highways, curbs, kilometer stones, guide-post, bridges, parking lots, warehouse marking and airport runway.

Approved: TIS-415-2008 BS-6044 Part 1: 1989

TYPE OF SURFACE

Concrete and asphalt

COLOR RANGE

White, Yellow, Red

FINISH

N/A.

VOLUME SOLID

N/A

COVERAGE



Approximately 8-15 square meters per gallon depending on the nature and porosity of the surface.

DRYING TIME*



5 Minutes max under normal drying conditions.

TRANSPORTATION & STORAGE

To avoid the risk of spillage, always store and transport in a secure upright position. Store away from heat and flame.

CLEANER

White spirit.

VOC CONTENT

High VOC content 25–50%

VOC's (Volatile Organic Compounds) contribute to atmospheric pollution.

EU limit value for this product (Cat A/g): 350g/l (2010). This product contains max 350g/l VOC.

THICKNESS

Wet: 50µm, dry: 28µm.

KEY PROPERTIES

- Binds powdery surfaces and resists alkali attack.
- An ideal primer for unpainted plaster and rendered surfaces.
- Suitable for exterior use.

PREPARATION

All surfaces to be painted should be clean, dry and free from loose and flaking material. Avoid inhalation of dust, wear a suitable face mask when dry sanding. Special precautions should be taken during surface preparation of pre-1960s paint surfaces over wood and metal as they may contain harmful lead. For further advice contact Customer Services. For additional information please visit our website www.ekviwat.com

APPLICATION



Stir well. Easy to apply by brush or roller. Do not apply over polystyrene surfaces.

CLEANING



Remove as much product as possible from application equipment before cleaning. Replace lid firmly. Clean equipment immediately after use with White Spirit or Turpentine Substitute. Some local authorities have special facilities for the disposal of waste coatings. Do not empty product into drains or watercourses.

PRECAUTIONS

- **FLAMMABLE**
- Contains 2-butanone oxime. May produce an allergic reaction.
- Safety data sheet available on request.
- Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- Repeated exposure may cause skin dryness or cracking.
- If medical advice is needed, have product container or label at hand.
- Keep out of reach of children.
- Dispose of contents/container to a waste disposal site in accordance with local/national regulations.
- Do not get in eyes, on skin, or on clothing.
- IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- IF ON SKIN: Wash with plenty of water. Do not use solvent thinners or White Spirit.
- IF SWALLOWED: Call a POISON CENTRE or doctor if you feel unwell.
- Ensure maximum ventilation during application and drying.
- Not recommended for interior use on large surface areas, or in confined spaces.
- Store in a well-ventilated place. Keep cool.
- Keep container tightly closed.

SIZES

5 Gallon

For further information and advice please call
Find out more at: www.ekviwat.com